

Installation Guide.

Single Sided Lightbox

This lightbox is designed to be mounted under an awning, veranda, ceiling or to a wall. You can drill your own screw points through the top of the lightbox or through the back. Keep fixings clear of wiring. Be sure to earth the lightbox housing.

These instructions apply to SKU AP-A-B-00XX

1. Choose Mounting Location

- a. Ensure the mounting surface is capable of supporting the lightbox.
- b. Confirm clearances and check for obstructions around the mounting point.

Warning: When mounting to or near a ceiling, allow sufficient clearance to insert the bolts and operate the tool needed to secure the end cap.

- c. Confirm the face will be able to slide out after installation. Only one end is removable.

2. Predrill

- a. Fit suitable anchors or brackets rated for the weight of the lightbox (Standard weight is 14.5kg for a 2000mm x 350mm x 100mm lightbox)
- b. Tighten securely.

3. Electrical Connection (Registered Electrician Only)

- a. Route electrical cable through the mounting surface so wires are hidden.
- b. Connect to the transformer inside the unit.
- c. Attach earth cable to the aluminium extrusion.
- d. Secure cables with strain relief to prevent pull-out.

4. Test & Close

- a. Check that the lightbox is level and secure.
- b. Electrician to connect to mains and test operation.
- c. Refit acrylic face and end cap if removed for wiring access.

⚠ Electrical Safety Notice

This lightbox must be hard-wired by a **registered electrician** in accordance with local electrical regulations.

Do not attempt to wire or power the unit yourself unless you are a licensed professional.

Failure to comply may result in electric shock, fire, or damage to the product and will void the warranty.